



OVERVIEW

This module is capable of covering more than 3000 BUS inputs divided into 8 areas to enhance security of house in many aspects. TIS Security Module allows automatic arm/disarm in different modes, including vacation, away, day, or night as it is equipped with a built-in clock.

KEY BENEFITS

- + Arm/Disarm security system in 5 modes (vacation, away, night, day, OFF)
- + Auto arming/disarming in different modes
- + Configurable with all sensors in TIS bus network.
- + Arming and alarm log recording.
- + Protection program available in vacation mode
- + Advanced Commands for Arming/Alarm situation

KEY FEATURES

- ★ Built-in timer with lasting battery.
- ★ Zone bypass function
- ★ Standard 35 mm din rail
- ★ Reverse Polarity Protection
- ★ Works with TIS-BUS protocol



BARCODE (UPC-A)



TIS SECURITY MODULE

Model: TIS-SEC-SM



PRODUCT SPECIFICATIONS		
	Security	<p>Levels: Vacation, Away, Night, Day, Disarm</p> <p>Arming commands: 20 for each level</p> <p>Alarm Commands: 20 for each alarm type</p> <p>Extra Alarms: Panic, blackout, freezing temperature, 3 channels addressable. (Burglary, Fire, Buzzer)</p> <p>Sirens and buzzer</p>
	Reaction time	approx. 30ms
	Function programmable options	<p>Other Functions: Auto Arm/Disarm, Entry/Exit Delay, Dial out Time, zone auto bypass, Duress Alarm</p>
	Mounting	<p>Din Rail: Standard 35 mm Din rail</p> <p>Wall mount: screw holder on the back of the module</p>
	Connection terminal	<p>Load and Power: Screw terminal 0,25...4mm²</p> <p>Data / bus: Male female connectors Link + screw Terminal</p>
	Weight	Without packaging: 0.22 KG
	Dimensions	Width x length x height: 90mm x 73mm x 76mm
	Housing	<p>Materials: Fire-proof ABS</p> <p>Casing color: Black Gray</p> <p>IP rating: IP 20</p>
	Temperature range	<p>Operation: -30...60°C</p> <p>Storage: -20...60°C</p> <p>Transport: -30...75°C</p>
	Air humidity	<85% non-condensing

