PRODUCT DATA <u>TI-DEK SATIN</u>



Washable Pure Acrylic Emulsion with a Satin Finish.

Appearance

Medium sheen.

Properties and Uses

Ti-Dek Satin is highly washable, has excellent flow and anti-splatter properties. It has a high opacity, low odour with excellent exterior and interior durability.

Surface Preparation

Essential for good paint performance is a sound substrate that has been properly cleaned and prepared. On existing painted surfaces to be redecorated, a small section of paint must be removed to establish the condition of the original paint and the substrate. Where there is doubt, the paint must be removed to a sound base.

Application Instructions

These instructions are issued as an aid in determining correct surface preparation, mixing and application procedure and should be closely followed to obtain maximum service from the material.

1. New Unpainted Wall Surfaces

e.g. Interior and exterior one coat plaster and interior two coat plaster (Cretestone) surfaces.

- (a) <u>1st coat</u>: Titanium Ti-Nyl Masonry Primer.
- (b) <u>2nd and 3rd coat</u>: Titanium Ti-Dek Satin.

2. Old Painted Areas

e.g. Interior and exterior one coat plaster.

- (a) Remove fungus growth, dust, loose and flaky material from the surface by means of a high pressure water jet. Allow the surface to dry properly.
- (b) <u>1st application</u>: Titanium Anti-Fungus Wash and allow to dry for 24 hours.
- (c) Fill imperfections with Titanium Ti-Fill.

<u>Note:</u> The use of cellulose fillers could result in dull patches in the finished paint film and premature failure of the system.

- (d) <u>1st coat</u>: Spot-prime with Titanium White Masonry Primer.
- (e) <u>2nd and 3rd coat</u>: Titanium Ti-Dek Satin.

Application Method:	Brush, roller or airless spray.
Spreading Rate:	± 10m ² per litre per coat on very smooth surfaces.
Cleaning of Utensils:	Wash immediately after use with warm soapy water.
Packaging Sizes:	20 L, 5 L and 1 L
Colour Range:	White and a variety of standard colours or any other Tint.

