

Standards

Name
Millberry Copper Scrap Wire

Standards
ASTM B115 - 10

Chemical composition

ASTM B115- 10 Standard for Millberry Copper Scrap Wire

Standard	Cu	Se	Te	Bi	Sb	Pb	As	Fe
Scrap Wire	99.97 - 99.99	≤0.0002	≤0.0002	≤0.0001	≤0.0004	≤0.0005	≤0.0005	≤0.001
		Ni	Sn	S	Ag			
		≤0.001	≤0.0005	≤0.0015	≤0.001			

Notes:

High purity, fine organization with low oxygen levels. Very good conductivity and thermal ductility, easy to hot and cold pressure-process. The Copper wire consists of clean (free of any insulation), unpinned, uncoated, unalloyed copper wire, free brittle burnt wire and excessive oils.

- ✓ Copper Millberry Scrap 99.99% (With minimum diameter of 2mm)
- ✓ Min. weight in each Container: 20,20MTS approx.
- ✓ Gross weight of each Container: 22.20MTS approximately.
- ✓ Packing: The goods must be arranged to ensure their safety during transport. Seller will ship the goods in packages, each container of 20"ft. with palletized banded by aluminium band.
- ✓ Special Note: All goods are packed in tons bags without being compressed.

