

ABSOLUTELY ECO-FRIENDLY



**GREENCOAT™**  
ECO PAINT

**FLOORGUARD**

## TECHNICAL AND MATERIAL SAFETY DATA SHEET

### DISCLAIMER AND IMPORTANT SAFETY NOTICE

To the best of our knowledge the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact GREENCOAT before ordering to ensure the correct products are used for application. No guarantee of accuracy is given nor implied. We guarantee that all GREENCOAT products have undergone quality control procedures to conform to GREENCOAT quality control standards. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to the replacement of products. Prices and cost data, if shown, are subject to change without prior notice. The factory will NOT be responsible for damage or loss if application is not done by GREENCOAT trained applicators or if GREENCOAT specifications are not adhered to. It is the customers' responsibility to ensure they familiarize themselves with the correct application methods and ask for help from GREENCOAT. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY GREENCOAT, EXPRESSOR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

### SUPPLIER IDENTIFICATION AND INFORMATION

<b>MANUFACTURER NAME</b>	<b>GREENCOAT</b>
<b>ADDRESS OF MANUFACTURING</b>	<b>7 VUYISILE MINI STREET, BETHAL, 2310</b>
<b>TEL NUMBER</b>	<b>071 482 2029</b>
<b>FAX NUMBER</b>	<b>017 647 6011</b>
<b>EMAIL</b>	<b>ADMIN@GREENCOAT.CO.ZA</b>

## PRODUCT IDENTIFICATION

Product name	Floorguard
Product Description	GREENCOAT Floorguard is a water-based, pure acrylic, quick-drying durable sealer and varnish for multiple surfaces. Suitable for spraying and brushing applications. The product is environmentally-friendly and does not emit noxious fumes and odours during and after application. A water clear, mid-sheen finish is available in 8 standard wood varnish colours.
Principal Characteristics	<ul style="list-style-type: none"> <li>• Acts as a hard-wearing membrane</li> <li>• Protective coating for tiles, walls, roofs and floors etc.</li> <li>• Waterproof coating for preserving natural surfaces</li> <li>• Lengthens life of roof, concrete, wood etc.</li> <li>• Protects surface against efflorescence</li> <li>• UltraViolet resistance</li> <li>• Stain resistance</li> <li>• Does not turn yellowish with age</li> <li>• Heat resistance</li> <li>• Very good adhesion</li> <li>• Non-toxic and odour free</li> </ul>
Intended use	It penetrates deep into the surface and reduces oil, grease, acids, and alkalis that see into the surface and cause deterioration. The acrylic resin enables it to bridge hairline and minor cracks within the substrate. Its versatility makes it suitable for a variety of applications, like primers, sealers and coatings for cementitious substrates and highly resistant marble stone finishes.

## COMPOSITION

TECHNICAL DATA	
% Solids by Volume	48%
Gloss	Semi - Gloss
Theoretical Spreading Rate DFT	10 - 15 m <sup>2</sup> per litre (1 coat depending on substrate.)
Colour	Wet - milky blue-white colour
Water Resistance	Excellent
Chemical Resistance	Good
Abrasion Resistance	Very good
Stain Resistance	Excellent
Flexibility	Excellent
Storage	Keep well-sealed at moderate temperatures
Cleaner	Water

## HAZARD IDENTIFICATION

Primary route of exposure	
Inhalation	No effects observed during application in confined space.
Eye contact	Direct contact with material can cause slight irritation.
Skin contact	<ul style="list-style-type: none"> <li>• Prolonged and repeated contact cause no irritation.</li> <li>• No specific symbols are required for the use of the products.</li> <li>• The products are not combustible or flammable and do not have specific acute, chronic or toxic effects on humans, nor are they harmful to the natural environment when released.</li> </ul>

## FIRST AID MEASURES

Eye contact	Flush eyes with large amount of water. If irritation persists, consult a physician.
Skin contact	Wash the skin with soap and water.
Ingestion	Drink plenty of water.

## FIRE-FIGHTING MEASURES

When applied on surfaces: Non-combustible, could act to retard the spread of flame.

Smoke toxicity index	Toxic gas factor - 1.0.
When cured (not applied)	Can burn.
Extinguishing agents	Normal foam, powder, water spray, or carbon dioxide (CO <sub>2</sub> ).

## ACCIDENTAL RELEASE MEASURES

Personal precautions	Follow normal safety precautions and if spillage occurs in a confined space, ensure there is adequate ventilation. There is no LD 50 data available for the products and the concentrations of particularly hazardous materials are so low that they are not considered a significant hazard under the recommended conditions of use.
Environmental precautions:	No environmental hazard when applied to surfaces or cured (solidified). No threat to freshwater or marine life.

## METHODS FOR CLEANING UP

- Contain the spillage with sand or earth.
- Take up spilled material (if possible) on a non-flammable absorbent (sand, earth, diatomite, chemical binders) and put in an appropriate container.
- Label the container with the waste designation and dispose according to the legislation - Do not use solvent.

## HANDLING AND STORAGE

Safe handling advice	Avoid direct contact with skin and eyes. Avoid inhalation and ingestion. Take personal protective measures and follow the protection and safety regulations. When working with coating products in a spray cabin, sufficient control of aerosols is unlikely and breathing apparatus such as respirators can be worn during spraying if preferred.
Measure to prevent fire	No specific preventative measures are required but keep the application area well ventilated.
Requirements for storage	Store in original containers (if possible) and keep tightly closed in a cool, dry, well-ventilated area. Although the products are not defined as dangerous goods, protect the products from direct extreme heat such as sources of ignition. Avoid direct sunlight and do not store in conditions below freezing point.
Shelf life	±2 years if well sealed.

## EXPOSURE CONTROLS / PERSONAL PROTECTION

### Occupational exposure limit:

OHSA PEL 15 mg/m (total dust), 5 mg/m (respiration fraction)

Personal protection	
Respiratory protection	Respiratory programme must be followed whenever workplace conditions warrant a respirator's use. Not required if airborne concentrations are maintained below exposure limit listed in exposure limit information.
Eye Protection	Safety glasses with impenetrable side shields are recommend.
Skin protection	Gloves may be used if required, but no known effects have been observed.

## STABILITY AND REACTIVITY

Stability	Stable when following the handling and storage recommendations.
Conditions to avoid	Avoid temperatures above 177°C, direct sunlight and Temperatures below freezing point for storage conditions.
Incompatibility	None known
Hazardous decomposition	By fire - carbon dioxide (CO <sub>2</sub> ) and carbon monoxide (CO).

## PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquids
Colours	Clear, Mahogany, Antique White, Imbuia, Dark Oak, Light Oak, Sapele, Oregon, Rose Wood, and Teak
Odour	Characteristic of the specific
PH	-8 -9
Reactivity	Salt fog resistant
UV Resistance/Weathering	75 000 hours - No visible breakdown
Density	> 1 gm/cm
Vapour density	Heavier than air
Solubility	Miscible in / with water prior to cure
Evaporation rate	< 1 water (see section 5)

## TOXICOLOGICAL INFORMATION / HEALTH EFFECTS

Acute toxicity	No known effects - health hazard rating in group 4 (minimal) of the Recommended Practice (ARP 006: 1991) guideline
Skin contact	No known effects
Eye contact	Splashes can cause eye irritation
Chronic toxicity	No known effects
Carcinogenicity	No known effects
Mutagenicity	No known effects
Neurotoxicity	No known effects
Reproductive hazards	No known effects
Additional information	The products have not been tested, but their classifications calculated according to conventional methods from the dangerous substances regulations. The products have been used to paint aquariums that house tropical fish and ponds that house Koi fish with no effects at all. The products do not emit noxious fumes or odour during and after application.

## ECOLOGICAL INFORMATION

Aquatic toxicity	No known effects
Biodegradability	Products are considered highly biodegradable, but not tested
Bioaccumulation:	No known effects
Mobility	Not tested
Additional information	The product is environmentally-friendly with a very low VOC (Volatile Organic Compound) as tested by the Huntingdon / SWL laboratories, Report number: 261394 - 23093 and described by America as a 'revolutionary breakthrough'.

## DISPOSAL CONSIDERATION

Disposal key	080103 – EWC waste from water-based paints.
Disposal method	Hand over empty packaging to an authorised disposal company / waste company – the waste regulations of the appropriate authorities are to be followed.

## TRANSPORT INFORMATION

ADR / FID (Road)	Not dangerous materials according to these regulations.
GGVSee / MDG (Maritime)	Not dangerous materials according to these regulations.
IATA (AIR)	Not dangerous materials according to these regulations.

## REGULATORY INFORMATION / EEC CLASSIFICATION

EEC hazard classification	None of the substances of the products are classified by the EEC as hazardous.
TSCA certification	All of the substances in the products are listed, or exempt from listing, on the TSCA.
National legislation	Pay attention to the Occupational Health and Safety Act.

## OTHER INFORMATION

All data is based on the current knowledge of GREENCOAT and describes the product with reference to safety data and is therefore not intended to guarantee certain properties.

## APPLICATION INSTRUCTIONS AND TECHNICAL DATA

These instructions are not intended to show product recommendations for specific services. They are issued as an aid in determining correct surface preparation and application procedures. It is assumed that the proper recommendations have been made. These instructions should be followed closely to obtain the maximum service from the material.

### Features Included

- Quick drying (overcoat 30 - 60 minutes)
- Excellent flexibility - will never harden.
- UltraViolet and weather resistant proof: 75, 000 hours +
- Good abrasion resistance
- Exceptional performance in wet weather.
- Colour fastness
- Zero flame spread

### Excellent resistance to

Acids, alkalis, water, salt solutions and solvents.

## Temperature resistance

Minus 50°C - 190°C. At 110°C loss of gloss is observed, and discoloration takes place, without loss of film integrity.

## APPLICATION

Suitability prepared concrete, metal and any surfaces as recommended.

### Compatible Coatings

A test patch is recommended before use of most coatings.

**Contact your GREENCOAT dealer for specific information.**

## REQUIREMENTS FOR STORAGE AND APPLICATION

Parameter	Storage (Unopened)	Paint	Substrate	Environment
% RH (Relative Humidity)	100 % Maximum	-	Min 2°C above dew point	85 % Max
Temp °C Min	5°C	5°C	5°C	5°C
Temp °C Min	40°C	40°C	40°C	40°C

## SURFACE PREPARATION

- All surfaces must be prepared using GREENCOAT Bind as a primer.
- Previously painted and old primed surfaces must be cleaned by removing all grease, paint and loose friable dirt with GREENCOAT Greenwash.
- Old enamel or oil painted surfaces should be sanded to a matt finish.
- Trial patches are required prior to full application.
- Patch prime where required with the appropriate primer.

**Application:** Suitable to apply with a pump sprayer.

---



**GREENCOAT CC**  
7 Vuyisile Mini Street, Bethal, 2310  
Customer Service Department [admin@greencoat.co.za](mailto:admin@greencoat.co.za)  
Facsimile 017 647 6011