


# wooden venetian blinds

## measuring instructions

For accurate measurements please use a metal tape measure, and take measurements in centimetres, to the nearest 0.1cm.


- All of our blinds can be fixed into the face of the window frame or wall, or into the top of the lintel - allowing you total control of the depth your blind can be positioned in the depth of your window recess.
- Choose whether you want the blinds to hang inside or outside the window recess.
- Please check for the proximity of adjacent walls, furniture, window handles etc. when measuring for your blinds.



**Recess**

### For blinds to hang inside the window recess:

Measure the drop by taking the measurement from the top of the recess to the window sill, in three places as shown. Measure the width of the window recess from wall to wall, in three places as shown. Take the smallest measurement. We will make all adjustments to ensure your blinds fit perfectly.



**Exact**

### For blinds to hang outside the window recess:

Measure the exact area you would like the blind to cover as shown.

## aftercare

Look after your blinds by following the straightforward operating instructions below.

### Operating

- One cord on the Wooden Venetian operates the height of the blind.
- The other cord operates the angle of the slats.
- To raise the blind pull the cord down until the blind reaches your desired height.
- To lower the blind pull the cord across the face of the blind to release the cordlock and let cord slide through your fingers.
- To adjust the angle of the slats pull the other cord until they are at the desired angle.
- When raising or lowering the blind slats should be in the open position.
- **Please note:** Wooden Venetians do not close totally - it is the nature of the product.

### Cleaning

- Your Wooden Venetians should only be cleaned with a dry non-lint cloth.

Your local supplier:

NB: The manufacturer will not accept responsibility for damage to blinds caused by misuse.  
Fitting items may vary depending upon type of fitting requested.