

אל פסק PROFIT

תכונות

- קומפקטי
- הגנה בפני נחשולי מתח בערך של 600 ג'אול -בלעדי
- מעבד מתקדם לאמינות גבוהה
- מייצב מתח רב דרגתי
- הפעלה אוטומטית לאחר הפסקת חשמל
- דמוי גל סינוס
- הדלקה קרה
- טעינה כאשר האל פסק כבוי
- התאמה לגנרטור (אופציה)
- שנה אחריות



Specifications

MODEL	PRO600-2	PRO800-2	PRO1000-2	PRO1500-2
CAPACITY	600 VA / 360 W	800 VA / 480 W	1000 VA / 600 W	1500 VA / 900 W
INPUT				
Voltage	220/230/240 VAC			
Voltage Range	162-290 VAC			
Frequency Range	60/50 Hz (auto sensing)			
OUTPUT				
Voltage	220/230/240 VAC			
AC Voltage Regulation (Batt. Mode)	±10%			
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz			
Transfer Time	Typical 2-6 ms			
Waveform (Batt. Mode)	Simulated Sinewave			
BATTERY				
Battery	12V / 7Ah	12V / 9Ah	2 x 12V / 7Ah	
Typical Recharge Time	4-6 hours recover to 90% capacity			
INDICATORS				
AC Mode	Green lighting			
Battery Mode	Green flashing			
ALARM				
Battery Mode	Sounding every 10 seconds			
Low Battery	Sounding every second			
Overload	Sounding every 0.5 second			
Fault	Continuously sounding			
PROTECTION				
Full Protection	Overload, discharge, and overcharge protection			
PHYSICAL				
Dimension, D X W X H (mm)	279 x 101 x 142		320 x 130 x 182	
Net Weight (kgs)	4.25	4.9	8.2	10.4
ENVIRONMENT				
Humidity	0-90 % RH @ 0- 40°C (non-condensing)			
Noise Level	Less than 40dB			
Standart	CE / EN62040-1 / EN62040-2			
USB	Support Windows 98 SE / ME / NT 4.x / 2000 / 2003 / XP / Vista / 2008/7/8/10 Linux according software list			

* Product specifications are subject to change without further notice